

PRODUCT NEWS

MULTIFIX 60

MULTIFIX 60

Bus bar system 60mm up to 630A

- a · *for copper bars of 12 – 30mm width and thickness of 5 – 10mm*
- a · *short circuit withstand tested to VDE 0660 part 500 and IEC 439-1*
- a · *current ratings up to 630A; AC 400V, AC 500V, AC 690V, 45 – 62 Hz*
- a · *3-, 4-, or 5-pole*



- a · *quick and easy direct installation of equipment for current distribution, ð saves time and costs for the user*
- a · *installation without an enclosure possible*
- a · *modern flexible system*
- a · *touch protection IP 2x due to compartmentalized cover system*
- a · *materials used are self extinguishing, free of halogen, phosphor, silicon and FCKW; marked for classified recycling*
- a · *installation of triple pole fuse elements:
D0, DII und DIII
component adapters + D0-fuse switch disconnectors TYTAN und CORON 2
NH-fuse switch disconnectors RST8 size 00 and 1 for direct installation on to bus bars
MULTIVERT 160A NH-vertical fuse switch disconnectors for direct installation on to 60mm bus bar systems*

PRODUCT NEWS

MULTIFIX 60 Bus bar system 60mm up to 630A

MULTIFIX 60



- a · **Component adapters –**
large adapter programme based on only 3 elements



- 1. Adapter base**
with cables 6 or 16mm²
- 2. Lateral extension part 9mm**
for individual extension of the adapter base of 9mm each
- 3. Universal supporting bar**
*in various widths
with clamp and expanding technique
top / bottom or front fixing*



- a · *infinite variable positioning*

- a · **Component adapters + D0-fuse switch disconnectors TYTAN I and II and CORON 2**
- a · *completely cabled and ready for installation*



a · TYTAN I and II



a CORON 2